


## Product Designation

Product Group:	Extraline conveyor and processing belts
Product Sub-Group:	Printing blankets
Main Industry Segments:	Textile printing
Belt Applications:	Printing blanket
Special Features:	High precision; Solvent resistant
Mode of Use/Conveyance:	Horizontal

## Product Design (enlarged)



## Product Construction/Design

1	Conveying Side (Material):	Thermoplastic polyurethane (TPU)
1	Conveying Side (Surface):	Smooth
1	Conveying Side (Property):	Non-adhesive
1	Conveying Side (Color):	Black
2	Traction Layer (Material):	Polyester (PET) fabric
	Number of Fabrics:	2
3	Running Side/Pulley Side (Material):	Polyester (PET) fabric
3	Running Side/Pulley Side (Surface):	Impregnated fabric
3	Running Side/Pulley Side (Color):	Gray

## Product Characteristics

Slider bed suitable:	Yes
Carrying rollers suitable:	Yes
Power turns, curved installations:	No
Nosebar suitable:	No
Low noise applications:	No
Antistatically equipped:	Yes
Metal detector suitable:	No
Flammability:	No specific flammability prevention property
Food suitability FDA:	No use intended
Food suitability USDA:	No use intended
Food suitability EU:	No

## Technical Data

<b>Thickness:</b>	2.15 mm	0.08 in.
<b>Mass of belt (belt weight):</b>	2.3 kg/m <sup>2</sup>	0.47 lbs./sq.ft
<b>Nosebar Radius (minimum):</b>	NA mm	NA in.
<b>Pulley diameter (minimum):</b>	80 mm	3.1 in.
<b>Pulley diameter minimum with counter flexion:</b>	80 mm	3.1 in.
<b>Tensile force for 1% elongation (k1% static) per unit of width (Habasit Standard SOP3-155 / EN ISO21181):</b>	18 N/mm	103 lbs./in.
<b>Tensile force for 1% elongation after relaxation (k1% relaxed) per unit of width (Habasit Standard SOP3-155 / EN ISO 21181):</b>	12 N/mm	69 lbs./in.
<b>Admissible tensile force per unit of width:</b>	16 N/mm	91 lbs./in.
<b>Operating temperature admissible (continuous):</b>	Min -15 °C Max 70 °C	Min 5 °F Max 158 °F
<b>Coefficient of friction on slider bed of pickled steel sheet:</b>	0.20 [-]	0.2 [-]
<b>Seamless manufacturing width:</b>	4000 mm	157 in.

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554), and are based on the Master Joining Method.

## Additional Technical Information

<b>Chemical Resistance Class:</b>	6 (These indications are not guarantees of properties)
<b>Installation and Handling Instructions:</b>	Follow the Installing and Maintenance Instructions which are supplied with each product delivery.; Install the slack belt and tension until running perfectly under the full belt load.; Maximum initial elongation; epsilon max.: 0.8%!; Recommended initial elongation 0.2 - 0.5%.
<b>Limitations:</b>	Use cleaning agent as prescribed by the machine or cleaning agent manufacturer.; This product has not been tested according to ATEX standards (atmospheres with explosion risk - ATEX 95 regulation or EU directive 94/9) and therefore is subject to user's analysis in the respective environment.

## Storage

For details consult 'Printing Blanket Handling Instructions' or contact Habasit.  
Store printing blankets in their original packaging protected from sunlight/light in a cool and dry place. Storage of printing blankets shall not exceed 2 years at above condition.

## Legend

*	No calculation Value
2)	Product containing different coating materials such as elastomer, natural fibers, silicones, etc., are not subject to the directive 2002/72/EC
3)	CLA: Coordination of the centre line-average value Ra (in the US also Arithmetical Average (AA)) to the maximum peak to valley height Rt for surfaces manufactured by chip removal.
8)	Due to high coefficient of friction of running/pulley side, the suitability for use on slider beds is limited German federal institute for risk assessment (Bundesinstitut fuer Risikobewertung)
EEC	European Economic Community
EU	European Union (Directive 2002/72/EC)
FDA	Food and Drug Administration
NA	Not available
NAP	Not applicable
USDA	United States Department of Agriculture (Food Safety and Inspection Service, Washington D.C.)
JFRL	Japan Food Research Laboratory

## Product Liability, Application Considerations

---

If the proper selection and application of Habasit products are not recommended by an authorized Habasit sales specialist, the selection and application of Habasit products, including the related area of product safety, are the responsibility of the customer. All indications / information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. The data provided herein are based on laboratory work with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experiences can lead to modifications and changes within a short time without prior notice.

BECAUSE CONDITIONS OF USE ARE OUTSIDE OF HABASIT'S AND ITS AFFILIATED COMPANIES CONTROL, WE CANNOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS MENTIONED HEREIN. THIS ALSO APPLIES TO PROCESS RESULTS / OUTPUT / MANUFACTURING GOODS AS WELL AS TO POSSIBLE DEFECTS, DAMAGES, CONSEQUENTIAL DAMAGES, AND FURTHER-REACHING CONSEQUENCES.

---