


Product Designation

Product Group:	Nonwoven conveyor and processing belts
Product Sub-Group:	Ulti-Mate belts for general conveying
Main Industry Segments:	Automotive general; General applications; Metal working; Various industries
Belt Applications:	Conveyor belt; Stamping belt; Transfer belt
Special Features:	Abrasion resistant; Cut resistant; Edges wear resistant; Excellent tracking characteristics; High abrasion resistance; Low noise applications; Non-marking; Oil resistant; Permanently antistatic
Mode of Use/Conveyance:	Horizontal; Slider bed

Product Design (enlarged)



Product Construction/Design

1 Conveying Side (Material):	Thermoplastic polyurethane (TPU)
1 Conveying Side (Surface):	Smooth
1 Conveying Side (Property):	Medium-adhesive; Ultra glossy
1 Conveying Side (Color):	Black
2 Traction Layer (Material):	Polyester (PET) scrim
Number of Fabrics:	0
3 Running Side/Pulley Side (Material):	Polyester (PET) fabric
3 Running Side/Pulley Side (Surface):	Buffed finish
3 Running Side/Pulley Side (Color):	Black

Product Characteristics

Slider bed suitable:	Yes
Carrying rollers suitable:	Yes
Power turns, curved installations:	No
Nosebar suitable:	No
Antistatically equipped:	Yes
Metal detector suitable:	No
Flammability:	No specific flammability prevention property
Food suitability FDA:	No use intended
Food suitability USDA:	No use intended
Food suitability EU:	

Technical Data

Thickness:	4.8 mm	0.190 in.
Mass of belt (belt weight):	4.5 kg/m ²	0.92 lbs./sq.ft
Nosebar Radius (minimum):	NA mm	NA in.
Pulley diameter (minimum):	100 mm	4 in.
Pulley diameter minimum with counter flexion:	150 mm	6 in.
Tensile force for 2% elongation (k2% static) per unit of width (Habasit standard QAD-WI-10-35):	24 N/mm	135 lbs./in.
Admissible tensile force per unit of width:	25 N/mm	140 lbs./in.
Operating temperature admissible (continuous):	Min -12 °C Max 80 °C	Min 10 °F Max 176 °F
Coefficient of friction on slider bed of pickled steel sheet:	NA [-]	[-]
Seamless manufacturing width:	1828.8 mm	72 in.

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity, per ASTM standards, and are based on the Master Joining Method.

Additional Technical Information

Chemical Resistance Class:	6 (These indications are not guarantees of properties)
Installation and Handling Instructions:	Install the slack belt and tension until running perfectly under the full belt load.
Limitations:	No dangers and limitations

Storage

For details consult 'Storage and handling requirements for belts and machine tapes' or contact Habasit. Protect belts from sunlight/UV-radiation/dust and dirt. Store spare belts in a cool and dry place and if possible in their original packaging.

Legend

*	No calculation Value
2)	Product containing different coating materials such as elastomer, natural fibers, silicones, etc., are not subject to the directive 2002/72/EC
3)	CLA: Coordination of the centre line-average value Ra (in the US also Arithmetical Average (AA)) to the maximum peak to valley height Rt for surfaces manufactured by chip removal. German federal institute for risk assessment (Bundesinstitut fuer Risikobewertung)
EEC	European Economic Community
EU	European Union (Directive 2002/72/EC)
FDA	Food and Drug Administration
NA	Not available
NAP	Not applicable
USDA	United States Department of Agriculture (Food Safety and Inspection Service, Washington D.C.)

Product Liability, Application Considerations

If the proper selection and application of Habasit products are not recommended by an authorized Habasit sales specialist, the selection and application of Habasit products, including the related area of product safety, are the responsibility of the customer. All indications / information are recommendations and believed to be reliable, but no representations, guarantees, or warranties of any kind are made as to their accuracy or suitability for particular applications. The data provided herein are based on laboratory work with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experiences can lead to modifications and changes within a short time without prior notice. BECAUSE CONDITIONS OF USE ARE OUTSIDE OF HABASIT'S AND ITS AFFILIATED COMPANIES CONTROL, WE CANNOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS MENTIONED HEREIN. THIS ALSO APPLIES TO PROCESS RESULTS / OUTPUT / MANUFACTURING GOODS AS WELL AS TO POSSIBLE DEFECTS, DAMAGES, CONSEQUENTIAL DAMAGES, AND FURTHER-REACHING CONSEQUENCES.